



CAPELLA

DIRECT VENT GAS FIREPLACE INSERT

TRIM OPTIONS

BLACK

PEWTER

VINTAGE COPPER VEIN

STYLING



SPLIT OAK LOG SET



ROCK COLLECTION



DECORATIVE STONE



DECORATIVE EMBER GLASS

| Model | IDV33N | IDV33LP | IDV36N | IDV36LP |
|---------------|------------|------------|------------|------------|
| Fuel | natural | propane | natural | propane |
| Input | 31,000 BTU | 28,500 BTU | 34,250 BTU | 30,000 BTU |
| Low | 20,900 BTU | 23,100 BTU | 24,000 BTU | 22,840 BTU |
| Output | 23,250 BTU | 21,375 BTU | 25,688 BTU | 22,500 BTU |
| Efficiency | 75% | 75% | 75% | 75% |
| FF (P 4 1-02) | 57.4% | 57.9% | 58.4% | 59.9% |

MINIMUM FIREPLACE OPENING

| MINIMUM FIREPLACE OPENING | | | | | | | | | |
|--|----------------------------------|---|----|---|--------------------------|---|--|--|--|
| | WIDTH | HEIGHT | DE | PTH | | | | | |
| IDV33 IDV36 | 26 ½" 30 ¾" | 21 ³ / ₈ " 25 ⁵ / ₈ " | | ³ / ₈ " | | | | | |
| MINIMUM UNIT COVERAGE | | | | | | | | | |
| IDV33 | WIDTH | HEIGHT | | IDV36 | WIDTH | HEIGHT | | | |
| IDV33 (Louvers) IDV33 (Clean View*) *Back Frame Dimension of C | 34 ½" 32 ¾" Clean View I | 24 ³ /8" 22 ³ /4" | | IDV36 (Louvers) IDV36 (Clean View*) | 39" 37 ¼" | 28 ³ / ₄ " 27" | | | |
| LOUVER KIT AND SURROUND SIZES | | | | | | | | | |
| IDV33 | WIDTH | HEIGHT | | IDV36 | WIDTH | HEIGHT | | | |
| I33LK (Louver Kit) I33S3426B (Surround) I33S4028B (Surround) I33S4430B (Surround) I33S4535B (Surround) | 40" 44" | 24 ³ / ₈ " 26 ¹ / ₂ " 28 ¹ / ₄ " 30 ⁵ / ₈ " 35" | | I36LK (Louver Kit) I36S3931B I36S4432B I36S4736B | 39" 39" 44" 47" | 28 ³ / ₄ " 31 ³ / ₄ " 32 ³ / ₈ " 36" | | | |
| CLEAN VIEW AND SURROUND SIZES | | | | | | | | | |
| IDV33 | WIDTH | HEIGHT | | IDV36 | WIDTH | HEIGHT | | | |
| I33CV (Clean View) | 35 ⁷ / ₈ " | 24 ¼" 29 ½" | | I36CV (Clean View) | 40" 43 ½" | 28 ½" 30 ¼" | | | |



39 %"

26"



The unit illustrated is a IDV33LP Direct Vent Fireplace Insert - Propane, MQROCK3 Contemporary Rock Collection - Multi Colored, MQRSP4 Rock Support Platform, I33CVPW Clean View Kit - Pewter, I33SSIPW Surround - Clean View - Pewter, IDV33PL Porcelain Reflective Liner.

I33SSI

Unit illustrated is a IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set, I33CVPW Clean View Kit

- Vintage Copper Vein, I33SS1PW Surround for Clean View
- Vintage Copper Vein, IDV33RL Refractory Brick Liner.

STANDARD FEATURES*

- > Dual Burner with glowing embers
- > Millivolt valve system allows operation during power failure with Hi-Low heat and flame adjustment
- > Matchless Piezo Ignition
- > Decorative Ash Bed
- > Ceramic Glass
- > On/Off Rocker switch
- > Heat activated blower with variable speed control
- > Mobile home, bedroom and bed sitting room approval

OPTIONAL FEATURES

 ${\color{red}{\sf Clean \ View \ Kit-Black, Pewter \ and \ Vintage \ Copper \ Vein}}$

Surrounds for Clean View – Black, Pewter and Vintage Copper Vein

Surround Picture Frame for Clean View – Black

Louver Kit for Grills – Grills available in Black, Classic Series Black with Antique, Chrome, or Polished Brass accents

Surrounds for Louver Kit - Black

Rock Sets* – Contemporary Collection in Natural, or Multi-Colored (Rock Support Platform required)

Log Set – Fibre Split Oak

Decorative Stones or Ember Chunks

(Glass Support Platform required)

Decorative Ember Glass* – White, Azuria (Blue), or Bronze (Glass Support Platform required)

Wall Mount Thermostat – Standard On/Off or Programmable 5 day (weekday) and 2 day (weekend)

Remote Control – On/Off, Thermostat, Modulating Thermostat.

Overlay Black Arch Door – Deluxe, Top Half, Double Arch and Double Door

Designer Doors – Arch or Straight with optional Antique, Chrome, or Polished Brass trims.

Kingsman Fireplaces, maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation Certification: The models IDV33 and IDV36 are certified for Canada/USA as a Vented Gas Fireplace Heater ANSI IZ21.88-2009, CSA 2.33-2009, CGA 217.491

"Components may have to be ordered separately to create a complete unit

